

EIFCO



DOUBLE - ENDED GRINDERS

SPECIFICATIONS

(All dimensions are in mm)

| MODEL | MG - 10 | MG - 12 | MG - 14 | MG - 16 |
|------------------------------------|------------------------|------------------|------------------|------------------|
| Size of Grinding Wheel : | | | | |
| For Vitrified Bond | 250 x 25 x 31.75 | 300 x 40 x 50.8 | 350 x 50 x 50.8 | 400 x 50 x 127 |
| For Resinoid Bond | ----- | 300 x 40 x 31.75 | 350 x 50 x 50.8 | 400 x 50 x 152.4 |
| Wheel Centre distance | 645 | 645 | 745 | 745 |
| Base to centre line of spindle | 860 | 860 | 860 | 860 |
| Diameter of spindle bearings | 35 | 35 | 40 | 40 |
| Power of Motor : | | | | |
| For Vitrified Bonded wheels | 1 HP | 2 HP | 3 HP | 5 HP |
| For Resinoid Bonded wheels | ----- | 3 HP | 5 HP | 7.5 HP |
| Speed of Motor | 1400 rpm | 1400 rpm | 1440 rpm | 1440 rpm |
| RPM of Grinding Wheels | | | | |
| For Vitrified Bonded wheels | 2292 rpm | 1910 rpm | 1637 rpm | 1432 rpm |
| For Resinoid Bonded wheels | ----- | 2864 rpm | 2455 rpm | 2148 rpm |
| Net Weight (approx.) | 400 kg | 410 kg | 550 kg | 580 kg |
| Gross Weight | 540 kg | 540 kg | 710 kg | 710 kg |
| Overall Dimension (LxBxH) | 745 x 565 x 1030 | 770 x 565 x 1050 | 870 x 695 x 1065 | 890 x 695 x 1095 |
| Electricals | 415V AC 3 Phase, 50 Hz | | | |

Note : In view of continuous development, we reserve the right to change the designs and/or dimensions without notice.



Manufactured by
EIFCO MACHINE TOOLS PRIVATE LIMITED

240, Mettupalayam Road, Coimbatore - 641 043, INDIA.

Phone : 0422 - 2442127, 6530318, 6530325

E-mail : contact@eifcomachinetools.com Web : www.eifcomachinetools.com