

EIFCO



DOUBLE - ENDED GRINDERS

SPECIFICATIONS

(All dimensions are in mm)

MODEL	MG - 10	MG - 12	MG - 14	MG - 16
Size of Grinding Wheel :				
For Vitrified Bond	250 x 25 x 31.75	300 x 40 x 50.8	350 x 50 x 50.8	400 x 50 x 127
For Resinoid Bond	-----	300 x 40 x 31.75	350 x 50 x 50.8	400 x 50 x 152.4
Wheel Centre distance	645	645	745	745
Base to centre line of spindle	860	860	860	860
Diameter of spindle bearings	35	35	40	40
Power of Motor :				
For Vitrified Bonded wheels	1 HP	2 HP	3 HP	5 HP
For Resinoid Bonded wheels	-----	3 HP	5 HP	7.5 HP
Speed of Motor	1400 rpm	1400 rpm	1440 rpm	1440 rpm
RPM of Grinding Wheels				
For Vitrified Bonded wheels	2292 rpm	1910 rpm	1637 rpm	1432 rpm
For Resinoid Bonded wheels	-----	2864 rpm	2455 rpm	2148 rpm
Net Weight (approx.)	400 kg	410 kg	550 kg	580 kg
Gross Weight	540 kg	540 kg	710 kg	710 kg
Overall Dimension (LxBxH)	745 x 565 x 1030	770 x 565 x 1050	870 x 695 x 1065	890 x 695 x 1095
Electricals	415V AC 3 Phase, 50 Hz			

Note : In view of continuous development, we reserve the right to change the designs and/or dimensions without notice.



Manufactured by
EIFCO MACHINE TOOLS PRIVATE LIMITED

240, Mettupalayam Road, Coimbatore - 641 043, INDIA.

Phone : 0422 - 2442127, 6530318, 6530325

E-mail : contact@eifcomachinetools.com Web : www.eifcomachinetools.com